

# Argus Security S.r.I. Via del Canneto, 14 34015 - Muggia (TS) - Italy info@argussecurity.it

# **UK Declaration of Performance - DoP**

Declaration in accordance to (UK) Construction Products Regulation No 305/2011

# UK Dichiarazione di Prestazione - DoP

Dichiarazione in conformità al regolamento sui prodotti da costruzione (Regno Unito) n. 305/2011

N°: TU1310UK

### 1. Unique identification code of the product-type:

Codice di identificazione unico del prodotto-tipo:

Product type: Input/Output Devices; Short-circuit Isolators; Wireless

Model Number and Description: TW-MTI-01 - TAURUS Wire To Wireless Translator Module Taurus Series

Operating Frequency Band: 868 MHz, 916 MHz

#### 2. Intended use/es:

Usi previsti:

**Fire Safety** 

Sicurezza Antincendio

#### 3. Manufacturer:

Fabbricante:

## **ARGUS SECURITY Srl**

Via del Canneto 14

Valle delle Noghere - 34015 Muggia - Trieste - Italy

info@argussecurity.it

www.argussecurity.it

# 4. Authorised representative:

Mandatario:

## Halma UK DS LTS

Misbourne Court, Rectory Way, Amersham

Bucks HP7 0DE, UK

## 5. System/s of AVCP:

Sistemi di VVCP:

System 1

## 6. Designated standard(s):

Norme Indicate:

EN 54-17: 2005

EN 54-18: 2005

EN 54-25: 2008 + AC:2012

#### 7. UK Approved Body/ies

Organismi Approvati dalla UK

DBI Certification-UK Ltd., No. 8504

Product code: TW-MTI-01 CoP Reference: 8504-UKCA-CPR-UKCSP10090

# 8. Declared performance/s:

Prestazioni Dichiarate:

ESSENTIAL CHARACTERISTICS	CLAUSE APPLICABLE	PERFORMANCE	DESIGNATED STANDARD
Performance parameters under fire conditions	5.2 <sup>(1)</sup>	PASS	
Operational reliability	4	PASS	1
Durability of operational reliability, temperature resistance	5.4, 5.5	PASS	
Durability of operational reliability, vibration resistance	5.9 to 5.12	PASS	EN 54-17: 2005
Durability of operational reliability, humidity resistance	5.6, 5.7	PASS	
Durability of operational reliability, corrosion resistance	5.8	PASS	
Durability of operational reliability, electrical stability	5.3, 5.13	PASS	
(1) This is assuming that the effect of the fire is to cause a short circuit in the transmission path that is protected by these devices			
ESSENTIAL CHARACTERISTICS	CLAUSE APPLICABLE	PERFORMANCE	DESIGNATED STANDARD
Response delay (response time)	5.2 <sup>(1)</sup>	PASS	
Performance under fire conditions	5.1.4	PASS	1
Operational reliability	5.1.4	PASS	EN 54-18: 2005
Durability of operational reliability, temperature resistance	5.3, 5.4	PASS	
Durability of operational reliability, vibration resistance	5.8 to 5.11	PASS	
Durability of operational reliability, humidity resistance	5.5, 5.6	PASS	
Durability of operational reliability, corrosion resistance	5.7	PASS	
Durability of operational reliability, electrical stability	5.2, 5.12	PASS	
(1) Response delays may not be a function of the input/output device, in which case no assessment is made as part of this standard			
ESSENTIAL CHARACTERISTICS	CLAUSE APPLICABLE	PERFORMANCE	DESIGNATED STANDARD
Performance parameters under fire conditions	4.1, 4.2.2, 5.2, 8.3.7	PASS	
Response delay (response time to fire)	8.2.3, 8.2.6	PASS	
Operational reliability	4.2.1, 4.2.3 to 4.2.7, 5.3, 5.4, 6, 7, 8.2.2, 8.2.4, 8.2.5, 8.2.7, 8.2.8 (a), 8.2.9, 8.3.1, 8.3.2, 8.3.3, 8.3.4, 8.3.5, 8.3.6	PASS	
Durability of operational reliability, temperature resistance	8.3.9 <sup>(b)</sup> , 8.3.10 <sup>(b)</sup> , 8.3.11	PASS	EN 54-25:2008
Durability of operational reliability, vibration resistance	8.3.16 <sup>(b)</sup> , 8.3.17 to 8.3.19	PASS	
Durability of operational reliability, humidity resistance	8.3.13 <sup>(c)</sup> , 8.3.14	PASS	
Durability of operational reliability, corrosion resistance	8.3.15 <sup>(b)</sup>	PASS	
Durability of operational reliability, electrical stability	8.3.20	PASS	
The products covered by this standard are assumed to enter the alarm condition, in an event of fire, before the fire becomes so large as			

The products covered by this standard are assumed to enter the alarm condition, in an event of fire, before the fire becomes so large as to affect their functioning. There is therefore no requirement to function when exposed to direct attack from fire.

<sup>(</sup>a) Only applicable to components required to indicate loss of communication or to transmit this information to the CIE.

<sup>(</sup>b) Not applicable for CIE

<sup>(</sup>c) Only applicable for CIE and smoke detectors

The performance of the products identified in point 1 in conformity with the declared performance in the point 8. This declaration is issued under the sole responsibility of the manufacturer identified in point 3.

La prestazione dei prodotti individuati al punto 1 è conforme alla prestazione dichiarata al punto 8. Tale dichiarazione è rilasciata sotto l'esclusiva responsabilità del fabbricante individuato al punto 3.

This document in available on website: www.argussecurity.it (section download for each product)

Questo documento è disponibile sul sito: www.argussecurity.it (nella sezione "download" di ogni prodotto)

# Signed for and on behalf of the manufacturer by:

Firmato a nome e per conto del Fabbricante da:

Technical Director
Mauro Ceppa

Trieste, Italy 02/05/2022