



## WIRELESS SOUNDER BASE


The TW-BS-01 Taurus Base Sounder unit is a high performance wireless sounder base that can be used as stand-alone notification device (with a blanking cap) or as a combined detection and alarm device when fitted with an integral Taurus optical, heat or multi detector. The TW-BS-01 unit has as standard 32+32 recognised sounder tones (primary and secondary) and 4 levels of volume adjustment, all of which can be easily configured on site. It is powered by standard lithium batteries and utilising well proven adaptive radio signal processing algorithms ensure the highest levels of life safety and reliability.



## **KEY FEATURES**

- Only compatible with Taurus detectors
- 32 tones settings (primary and secondary for alert and evacuation), selectable via onboard dip switches
- 4 volume levels
- Bi-directional wireless communication
- Can be used with Taurus addressable and conventional translators
- 22 pairs of field channels
- Long communication range (≅1 km in open air)
- Dual channel redundancy
- 5 year battery life (including 10 seconds weekly test)
- Utilises standard low-cost lithium battery technology
- Device identification tab
- Easy scan & link programming option
- Security screw to prevent tampering and unwanted removal
- 3rd party approval to EN54-3 and EN54-25
- Red and white blanking cap options
- 5 year product warranty

## **TECHNICAL INFORMATION**



Version [2] Page 1 of 2

| TECHNICAL SPECIFICATION       |                           |
|-------------------------------|---------------------------|
| Operating frequency range     | 868 - 870 MHz             |
| Max radiated power            | 14dBm (25mW)              |
| IP rating                     | 21C                       |
| Weight (without batteries)    | 224 g                     |
| Batteries                     | 2x CR123A (3 V & 1.2 Ah)  |
| Battery lifespan (typical)    | 5 years                   |
| Dimensions                    | 129 mm x 54 mm            |
| Operating Temperature         | -10°C to +55°C            |
| Max humidity (non condensing) | 95% RH                    |
| Sound Output (typical)        | 88-91dBA (tone dependent) |

# **STANDARDS & APPROVALS**

- EN54-25: Components using radio links and system requirements
- EN54-3: Fire alarm devices



# **ORDER CODE**

TW-BS-01

TAURUS WIRELESS SOUNDER BASE

# **BLANKING CAP OPTIONS**



White blanking cap (LID100-SG/W)



Red blanking cap (LID100-SG/R)

Check if this document is up to date

 $Argus\ Security\ Srl,\ Via\ del\ Canneto,\ 14,\ 34015\ Muggia,\ (TS),\ Italia\ T: +39-040.23.96.411,\ E: info@argus security.it,\ W:\ www.argus security.it$ 

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.

Version [2] Page 2 of 2