DATASHEET WIRELESS VAD & SOUNDER BASE, WHITE LED

TW-BSB-23W-01

The TW-BSB-23W-01 Taurus Wireless VAD & Sounder Base is a high performance device, incorporating an EN54-23 compliant VAD used to alert people in the event of a fire. Each unit has an integral moulded base for mounting an wireless detector or a sounder cover if a detector is not required. The unit has as standard 32 recognised sounder tones (primary and secondary) and 4 levels of volume adjustment, as well as high power/low power visual settings, all of which can be easily configured on site.

Powered by standard lithium batteries and utilising well proven adaptive radio signal processing algorithms ensure the highest levels of life safety and reliability.







KEY FEATURES

- Only compatible with Taurus detectors
- 32 tones settings (primary and secondary for alert and evacuation), selectable via onboard dip switches
- 4 volume levels
- Bi-directional wireless communication
- Can be used with Taurus addressable and conventional translators
- 22 pairs of field channels
- Dual channel redundancy
- Long communication range (≅1 km in open air)
- 5 year battery life (including weekly test)
- Utilises standard low-cost lithium battery technology
- Easy scan & link programming option
- Security screw to prevent tampering and unwanted removal
- 3rd party approval to EN 54-3 and EN 54-23
- Red and white blanking cap options
- 5 year product warranty

TECHNICAL INFORMATION





Argus Security S.r.l. Via del Canneto, 14 34015 Muggia (TS) Italy

T: +39-040.23.96.411 E: info@argussecurity.it www.argussecurity.it

TECHNICAL SPECIFICATION

| Operating frequency range | 868 – 870 MHz |
|---|--------------------------|
| Max radiated power | 14dBm (25mW) |
| IP rating | 21C |
| Weight (without batteries) | 244 g |
| Batteries | 2x CR123A (3 V & 1.2 Ah) |
| Battery lifespan (typical) | 5 years |
| Dimensions | 129 mm x 54 mm |
| Operating Temperature | -10°C to +55°C |
| Max humidity (non condensing) | 95% RH |
| Sound Output (typical) | 88-91dBA (tone depende |
| 2 EN 54-23 compliant visual settings | high power/low power |
| High power | C-3-15/ O-4.6-15 |
| Low power | C-3-10 |
| | |

STANDARDS & APPROVALS

- EN 54-3: Fire alarm devices Sounders
- EN 54-23: Fire alarm devices Visual alarm devices
- EN 54-25: Components using radio links









DATASHEET WIRELESS VAD & SOUNDER BASE, WHITE LED

TW-BSB-23W-01

BLANKING CAP OPTIONS



White blanking cap (LID100-SG/W)



Red blanking cap (LID100-SG/R)

Argus Security S.r.l. Via del Canneto, 14 34015 Muggia (TS) Italy

T: +39-040.23.96.411 E: info@argussecurity.it www.argussecurity.it



